

23/06/2025

Steiner BUHLER



Modell MTSC-65/120 Kapazität: 6 Tonnen/Stunde

Kategorien: [Brauerei](#), [Herstellung](#), [Müllerei und Sudhaus](#)

Produktgalerie:

Parc Activité du Chat 59118 WAMBRECHIES (FRANCE) Téléphone : +33 320 93 66 71
Email : info@wallart.fr

23/06/2025



High versatility.

The Euler MTSD destoner is applied for efficient separation of stones and pebbles, glass, and other high-density matter from the stream of grain. The throughput capacity will vary as a function of the specific product and its degree of contamination. With soft wheat, a throughput up to 22 t/h can be achieved, with durum wheat up to 14.5 t/h, and with cornmeal up to 16.5 t/h. In addition to the grain varieties mentioned, the destoner is also used to process rye, rice, and soybeans.

High separating efficiency – excellent grain cleaning.

- With its high separating efficiency, the MTSD destoner is capable of efficiently separating even small and light-weight particles with the size of a grain from the stream of product, thus ensuring optimal grain cleaning.
- The excellent separation of high-density particles such as stones and pebbles, glass, and metal allows wear and tear of the downstream elements within the production chain to be appreciably reduced.
- Carefully cleaned raw materials are a precondition for achieving a high end product purity and complying with food safety regulations.

Wide variety of applications.

This destoner is recommended for its wide variety of models.

Tailor-made solutions – optimal customization.

The MTSD destoner is available in three different sizes with a throughput capability of 2 to 6 t/h, 6 to 12 t/h, or 12 to 22 t/h. It can thus be flexibly adjusted to individual space situations.



MTSD destoner for efficient separation of stones and pebbles

The advantages at a glance:

The technical data of the Destoner MTSD at a glance:

Model	MTSD-65/120-E	MTSD-65/120	MTSD-120/120
Dimensions			
A	1600	1600	1600
B	1000	1000	1040
C	1100	1440	1440
D	1040	1000	1000
E	860	860	1000
F	200	300	300
G	100	120	120
Screen width	mm	85	85
Screen length	mm	120	120
Drive	kW	1.4/0.2	1.4/0.2
Regulative air pressure	bar	12	12
Approx. weight	kg	210	400
net			600

(Values including or without dimensions, technical data, weight, etc.)



Capacity range:

Model	MTSD-65/120-E	MTSD-65/120	MTSD-120/120
Soft wheat			
Throughput	t/h	0 - 12	12 - 22